APPLICATION FOR PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA

Date	e of filing in State Engineer's Office APR 25 1977
Retu	rned to applicant for correction
	rected application filed
Мар	filed APR 2.5 1977
	The applicant David Beebe and Gerald Beebe
	7985 W. Craig Road , of Las Vegas City or Town
	Nevada 89108 , hereby make S application for permission to appropriate the public State and Zip Code No.
wate	ers of the State of Nevada, as hereinafter stated. (If applicant is a corporation, give date and place of incorpora-
tion;	; if a copartnership or association, give names of members.)
1.	The source of the proposed appropriation is an underground source in the Las
	Name of stream, lake or other source. Vegas basin
2.	
۷.	The amount of water applied for is
•	The water to be used for domestic & quasi-municiple purposes
	Irrigation, power, mining, manufacturing, domestic, or other use.
4.	If use is for:
	(a) Irrigation (state number of acres to be irrigated)
	(b) Stockwater (state number and kinds of animals to be watered)
	(c) Other use (describe fully under "No. 12, Remarks")
	(d) Power:
	(1) Horsepower developed
	(2) Point of return of water to stream
5.	The water is to be diverted from its source at the following point: within the NW4 SE4 of S.
	4. T. 20S., R. 60 E., M.D.B.&M., at a point from which the center Describe as being within a 40-acre subdivision of public survey, and by course and distance to a section corner. If on unsurveyed land,
	section corner bears North 42 degrees 07' West a distance of
6.	it should be stated. 278.0 feet. Place of use within the NWA SEM of Section 4. Township 20 South. Describe by legal subdivision, if on unsurveyed land it should be so stated.
	Describe by legal subdivision, if on unsurveyed land it should be so stated. Range 60 East, M.D.B.&M.
	·
7.	Use will begin about January 1 and end about December 31 of each year
_	Use will begin about January 1 and end about December 31 , of each year. Day and Month Day and Mont
8.	Description of proposed works. (Under the provisions of NRS 535.010 you may be required to submit plans and
	specifications of your diversion or storage works.) well, casing, pump, pressure tank
	and distribution pipeline State manner in which water is to be diverted, whether by dam or other works, whether through pipes, ditches, flumes, or other conduits.

9. Estimated cost of works	\$7,000.00			
0. Estimated time required to	construct works2 ye	ars		
1. Estimated time required to	Estimated time required to complete the application to beneficial use 3 years			
Remarks: For use other t consumptive use.	Remarks: For use other than irrigation or stock watering, state number and type of units to be served or annual consumptive use.			

Applicant David Beebe 8				
Compared 1m/ga	By dc/ga	s/Stephen F. Turner Stephen F. Turner 2325 W. Charleston Blvd. Las Vegas, Nevada 89102		
	APPROVAL OF			
This is to certify that I he	•	plication, and do hereby grant the same, subject to the		
-		pheation, and do hereby grant the same, subject to the		
collowing limitations and condition	ions:			
		existing rights and is when water can be furnished		
by an entity such a	as a water district	or a municipality engaged		
in furnishing water discharge pipeline	. A totalizing me	ter must be installed in the diversion, and accurate		
measurements must k	oe kept of water pl	aced to beneficial use. It		
		low for a reasonable lowering		
of the static water 2-inch opening for	r level. The well measuring depth to	shall be equipped with a water. If the well is		
<pre>2-inch opening for flowing, a valve mu</pre>	measuring depth to ust be installed an	water. If the well is d maintained to prevent		
2-inch opening for flowing, a valve mu waste. This source	measuring depth to ust be installed and is located within	water. If the well is d maintained to prevent an area designated by the		
2-inch opening for flowing, a valve mu waste. This source State Engineer purs right to regulate t	measuring depth to ust be installed and is located within suant to NRS 534.03	water. If the well is d maintained to prevent		
2-inch opening for flowing, a valve muwaste. This source State Engineer pursuight to regulate tand all times.	measuring depth to ust be installed and is located within suant to NRS 534.03 the use of the wate	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any		
2-inch opening for flowing, a valve muwaste. This source State Engineer pursuight to regulate tand all times.	measuring depth to ust be installed and is located within suant to NRS 534.03 the use of the wate	water. If the well is d maintained to prevent an area designated by the 0. The State retains the		
2-inch opening for flowing, a valve muwaste. This source State Engineer pursuight to regulate tand all times.	measuring depth to ist be installed and is is located within suant to NRS 534.03 the use of the wate	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any		
2-inch opening for Flowing, a valve muvaste. This source State Engineer pursuight to regulate than all times.	measuring depth to 1st be installed an 2 is located within 3 suant to NRS 534.03 4 the use of the wate	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any		
2-inch opening for flowing, a valve mu waste. This source State Engineer pursuight to regulate than all times.	measuring depth to 1st be installed an 2 is located within 3 suant to NRS 534.03 4 the use of the wate	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any		
2-inch opening for flowing, a valve mu waste. This source State Engineer pursuight to regulate tand all times.	measuring depth to ust be installed and e is located within suant to NRS 534.03 the use of the wate	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any		
2-inch opening for flowing, a valve mu waste. This source State Engineer pursuight to regulate tand all times.	measuring depth to ist be installed and e is located within suant to NRS 534.03 the use of the wate	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any		
2-inch opening for Flowing, a valve mu waste. This source State Engineer pursuight to regulate than all times. The amount of water to be app	measuring depth to ust be installed and e is located within suant to NRS 534.03 the use of the wate propriated shall be limited to the	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and		
2-inch opening for flowing, a valve mu waste. This source State Engineer pursuight to regulate the and all times. The amount of water to be apposed to exceed.	measuring depth to 1st be installed and 2 is located within 3 uant to NRS 534.03 the use of the wate propriated shall be limited to the 0.01 cubic to	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second, but not to exceed		
2-inch opening for Flowing, a valve muvaste. This source State Engineer pursuight to regulate the and all times. The amount of water to be apport to exceed.	measuring depth to 1st be installed an 2 is located within 3 suant to NRS 534.03 the use of the wate propriated shall be limited to the 0.01 cubic to the annually.	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second, but not to exceed		
2-inch opening for Flowing, a valve muvaste. This source State Engineer pursuight to regulate the and all times. The amount of water to be apport to exceed.	measuring depth to 1st be installed an 2 is located within 3 suant to NRS 534.03 the use of the wate propriated shall be limited to the 0.01 cubic to the annually.	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second, but not to exceed		
2-inch opening for Flowing, a valve mu waste. This source State Engineer pursuight to regulate the and all times. The amount of water to be apposed to exceed. 2.73 million gallor Actual construction work shall be apposed to the state of the amount of water to be apposed to exceed.	measuring depth to ust be installed and e is located within suant to NRS 534.03 the use of the wate propriated shall be limited to the 0.01 cubic to the annually.	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second, but not to exceed		
2-inch opening for flowing, a valve muste. This source State Engineer pursuight to regulate the and all times. The amount of water to be appoint to exceed. 2.73 million gallor Proof of commencement of workstall by the state of the state	measuring depth to 1st be installed and 2 is located within 3 suant to NRS 534.03 3 the use of the wate propriated shall be limited to the 0.01 cubic for annually. Degin on or before	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second, but not to exceed October 17, 1977		
2-inch opening for Flowing, a valve muy waste. This source State Engineer pursuight to regulate the and all times. The amount of water to be apposed to exceed 2.73 million gallor Proof of commencement of work work must be prosecuted with the source of	measuring depth to 1st be installed and 2 is located within 3 suant to NRS 534.03 3 the use of the wate propriated shall be limited to the 0.01 cubic for annually. Degin on or before	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second, but not to exceed October 17, 1977 November 17, 1977 npleted on or before October 17, 1977		
2-inch opening for flowing, a valve mustaste. This source State Engineer pursuight to regulate the and all times. The amount of water to be appoint to exceed. 2.73 million gallor Actual construction work shall be prosecuted with a proof of completion of work shall be	measuring depth to 1st be installed and 2 is located within 3 suant to NRS 534.03 3 the use of the wate propriated shall be limited to the 0.01 cubic to the annually. Degin on or before	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second, but not to exceed October 17, 1977 November 17, 1977 npleted on or before October 17, 1977		
2-inch opening for flowing, a valve mustaste. This source State Engineer pursuight to regulate the and all times. The amount of water to be appoint to exceed. 2.73 million gallor Proof of commencement of work work must be prosecuted with the Proof of completion of work shall be proof of completion of water to beneficiate the completion of water to beneficial contents.	measuring depth to 1st be installed and 2 is located within 3 suant to NRS 534.03 3 the use of the wate propriated shall be limited to the 0.01 cubic for annually. Degin on or before	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second, but not to exceed October 17, 1977 November 17, 1977 November 17, 1977 November 17, 1977		
2-inch opening for flowing, a valve must be prosecuted with a pplication of water to beneficier of the application of water to be application of water to	measuring depth to 1st be installed and 2 is located within 3 uant to NRS 534.03 the use of the wate propriated shall be limited to the 0.01 cubic to ans annually. Degin on or before	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second, but not to exceed October 17, 1977 November 17, 1977 November 17, 1977 November 17, 1977 October 17, 1977 October 17, 1977 November 17, 1977 October 17, 1977		
2-inch opening for flowing, a valve mustate. This source State Engineer pursuight to regulate the and all times. The amount of water to be appoint to exceed. O.73 million gallor Actual construction work shall be proof of commencement of work work must be prosecuted with a proof of completion of work shall be proof of the application of water to beneficially proof of the application of water to beneficially proof of beneficial use filed. DECOMMENDED TO DECOMMENDED	measuring depth to 1st be installed and 2 is located within 3 suant to NRS 534.03 3 the use of the wate propriated shall be limited to the 0.01 cubic for annually. Degin on or before. Reasonable diligence and be contail be filed before. all use shall be made on or before to beneficial use shall be filed on or located and the contained are shall be filed on or located as shall be filed	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second, but not to exceed October 17, 1977 November 17, 1977 November 17, 1977 November 17, 1977 October 17, 1979 I on or before October 17, 1979		
2-inch opening for flowing, a valve muste. This source State Engineer pursuight to regulate the and all times. The amount of water to be appoint to exceed. O.73 million gallor Actual construction work shall be proof of commencement of work must be prosecuted with a Proof of completion of work shall be proof of the application of water to beneficially proof of the application of water to be proof of the application of work filed. DECOMPLETION OF WORK filed.	measuring depth to 1st be installed and 2 is located within 3 uant to NRS 534.03 3 the use of the wate oropriated shall be limited to the 0.01 cubic to a annually. Degin on or before. k shall be filed before. reasonable diligence and be contall be filed before. all use shall be made on or before to beneficial use shall be filed on or left to beneficial use shall be filed to the left to beneficial use shall be filed to the left to beneficial use shall be filed to the left to beneficial use shall be filed to the left to beneficial use shall be filed to the left to beneficial use shall be filed to the left to be the left to be	water. If the well is d maintained to prevent an area designated by the 0. The State retains the r herein granted at any me amount which can be applied to beneficial use, and feet per second. but not to exceed October 17, 1977 November 17, 1977 November 17, 1977 October 17, 1979 I on or before October 17, 1979 I on or before November 17, 1979 Before November 17, 1979 Defore November 17, 1979		